

# Triflex Than Primer 533



## Use

Primer for PVC substrates for Triflex SmartTec systems

## Properties

- Cold liquid applied
- Fast curing
- Fast overcoat time

## Components

Component	Product
Resin	Triflex Than Primer 533

## Packaging

Component	Pack size
Resin	Drum: 0.40Litres

## Colour(s)

Brownish.

## Application conditions

Condition	Value
Ambient and substrate temperature	+10°C to +35°C

## Substrate assessment / pretreatment / preparation

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Specification proposal.

## Application method

Brush/roller.

## Consumption

0.10L/m<sup>2</sup> minimum – refer to Triflex Specification proposal.

**Note:** Consumption based on smooth, even, non-absorbent substrate.

## Curing time (at 20°C)

Condition	Time
Can be on / over-coated	Approximately 20 minutes to 12 hours

## Interruptions during works

If the surface is to be recoated after approximately 12 hours, repeat the application.

## Tool cleaning

Clean tools with Triflex Cleaner.



## Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 6 months.

## Health and safety

Refer to Safety Data Sheets.

## Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

## Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.