



MAIN AREA WATERPROOFING



NOTES

- 1 TRIFLEX PROFIBRE® @ 3.00 Kg/m² MIN. TO ENCAPSULATE FIXINGS - APPLIED IN TWO APPLICATIONS @ 1.50 Kg/m² MIN.
- 2 TRIFLEX PROFIBRE® TO CREATE A GASKET WASHER




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX PROPARK HD RAMP WITH EMERY 1.0-3.0mm

PROJECT

STANDARD

DETAIL

SURFACE MOUNTED DETAIL - INSTALLATION AFTER PROTECTION AND SURFACING

DRAWING NUMBER

PROPARK HD RAMP_043
_SURFACE MOUNTED DETAIL
- INSTALLATION AFTER
PROTECTION AND SURFACING

SCALE

NTS

DATE


10/08/2018

Triflex

Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



CAR PARK | MARKINGS | REPAIRS