



DETAIL PROTECTION



TRIFLEX PRODETAIL[®] @ 3.00 Kg/m² MIN.
 TRIFLEX 110g REINFORCEMENT FLEECE
 TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
 GENERIC DIMENSIONALLY STABLE / SUITABLE SUBSTRATE (PREPARED)


MAIN AREA WATERPROOFING



OPTIONAL: TRIFLEX MICROCHIPS @ 0.05 Kg/m²
 TRIFLEX CRYL FINISH 205 @ 0.60 Kg/m² MIN. (TRIFLEX QUARTZ 0.7 - 1.2mm)
 0.55 Kg/m² MIN. (TRIFLEX QUARTZ 0.4 - 1.2mm)
 TRIFLEX PROFLOOR RS @ 4.00 Kg/m² MIN. WITH TRIFLEX QUARTZ (0.7 - 1.2mm / 0.4 - 1.2mm) @ 5.00 Kg/m² APPROX.
 TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
 GENERIC DIMENSIONALLY STABLE / SUITABLE SUBSTRATE (PREPARED)

NOTES

1 GRATING RELIEVED IF REQUIRED TO ALLOW CLEARANCE




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX BFS COLOURSEAL - LARGE GRAIN QUARTZ

PROJECT

STANDARD

DETAIL

DRAINAGE CHANNEL ENCAPSULATED

DRAWING NUMBER

BFS_CS_LGQ_153
 _DRAINAGE CHANNEL ENCAPSULATED

SCALE

NTS

DATE


11/05/2016

Triflex

Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
 ST15 8JS | Tel: 01785 819119
 www.triflex.co.uk | info@triflex.co.uk



WALKWAYS | BALCONIES | TERRACES