



**DETAIL PROTECTION**



- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (REFER TO PROJECT SPECIFICATION)
- OUTLET LINER / SPIGOT (PREPARED)
- CONCRETE SUBSTRATE (PREPARED)


**MAIN AREA PROTECTION AND SURFACING**



- TRIFLEX CRYL FINISH 209 @ 0.55 Kg/m² MIN.
- TRIFLEX CRYL RS 246 @ 2.40 Kg/m² MIN. WITH TRIFLEX QUARTZ (0.4 - 1.2mm) EMBEDDED @ 5.00 Kg/m²
- TRIFLEX PRIMER IF REQUIRED (REFER TO PROJECT SPECIFICATION)
- CONCRETE SUBSTRATE (PREPARED)

**NOTES**

- 1 LIFT OUTLET COVER / GUARD TO ALLOW FOR PREPARATION, PRIMING AND WATERPROOFING INSTALLATION AND REINSTATE




**GENERAL NOTES**

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex PROJECT specification and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

**INDICATIVE SYSTEM BUILD-UP**



**SYSTEM**

TRIFLEX DCS-C WITH QUARTZ 0.4 - 1.2mm

**PROJECT**

STANDARD

**DETAIL**

FLUSH OUTLET

**DRAWING NUMBER**

DCS-C WITH QUARTZ\_105 \_FLUSH OUTLET

**SCALE**

NTS


**DATE**

04/01/2018



Triflex (UK) Limited

Whitebridge Way | Stone | Staffs  
ST15 8JS | Tel: 01785 819119  
www.triflex.co.uk | info@triflex.co.uk



CAR PARK | MARKINGS | REPAIRS