



DETAIL PROTECTION




MAIN AREA PROTECTION AND SURFACING



NOTES


- 1 MAKE GOOD WITH TRIFLEX CRYL PASTE
- 2 TRIFLEX PROFIBRE® @ 3.00 Kg/m² MIN. TO ENCAPSULATE FIXINGS APPLIED IN TWO APPLICATIONS @ 1.50 Kg/m² MIN.



GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex PROJECT specification and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.



SYSTEM

TRIFLEX DCS-C WITH QUARTZ 0.4 - 1.2mm

PROJECT

STANDARD

DETAIL

SURFACE MOUNTED DETAIL - LESS CRITICAL UPSTAND

DRAWING NUMBER


DCS-C WITH QUARTZ_041_ SURFACE MOUNTED DETAIL - LESS CRITICAL UPSTAND

SCALE	DATE
NTS	04/01/2018



Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
 ST15 8JS | Tel: 01785 819119
 www.triflex.co.uk | info@triflex.co.uk



CAR PARK | MARKINGS | REPAIRS