



DETAIL PROTECTION




- TRIFLEX CRYL FINISH 209 (THIXO IF VERTICAL > 250mm) @ 0.50 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX PRIMER (REFER TO PROJECT SPECIFICATION)
- GENERIC SUBSTRATE (PREPARED)

DETAIL PROTECTION



- TRIFLEX PRECO CRYL REIBEPLASTIK @ 4.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX PRIMER (REFER TO PROJECT SPECIFICATION)
- GENERIC SUBSTRATE (PREPARED)


MAIN AREA PROTECTION AND SURFACING



- TRIFLEX CRYL FINISH 209 @ 0.55 Kg/m² MIN.
- TRIFLEX CRYL RS 246 @ 2.40 Kg/m² MIN. WITH TRIFLEX QUARTZ (0.4 - 1.2mm) EMBEDDED @ 5.00 Kg/m²
- TRIFLEX PRIMER IF REQUIRED (REFER TO PROJECT SPECIFICATION)
- CONCRETE SUBSTRATE (PREPARED)

NOTES

- 1 MECHANICAL DAMAGE TO BE TREATED AS MAINTENANCE ITEM




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex PROJECT specification and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX DCS-C WITH QUARTZ 0.4 - 1.2mm

PROJECT

STANDARD

DETAIL

KERB - FULLY ENCAPSULATED - HIGH VISIBILITY MAINTENANCE COATING

DRAWING NUMBER

DCS-C WITH QUARTZ_023_KERB - FULLY ENCAPSULATED - HIGH VISIBILITY MAINTENANCE COATING

SCALE

NTS

DATE

04/01/2018



Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



CAR PARK | MARKINGS | REPAIRS