



DETAIL WATERPROOFING



- TRIFLEX PRODETAIL® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- OUTLET LINER / SPIGOT (PREPARED)
- GENERIC SUBSTRATE


MAIN AREA WATERPROOFING



- TRIFLEX MICROCHIPS @ 0.05 Kg/m²
- TRIFLEX CRYL FINISH 205 @ 0.50 Kg/m² MIN.
- TRIFLEX PROFLOOR RS @ 4.00 Kg/m² MIN.
- TRIFLEX PROTERRA® @ 3.00 Kg/m² MIN.
- TRIFLEX 110g REINFORCEMENT FLEECE
- TRIFLEX PRIMER (IF REQUIRED - REFER TO PROJECT SPECIFICATION PROPOSAL)
- GENERIC DIMENSIONALLY STABLE / SUITABLE SUBSTRATE (PREPARED)

NOTES

- 1 LIFT OUTLET COVER / GUARD TO ALLOW FOR PREPARATION, PRIMING AND WATERPROOFING INSTALLATION AND REINSTATE




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX BTS-P MICROCHIPS

PROJECT

STANDARD

DETAIL

WADE TYPE FLUSH OUTLET

DRAWING NUMBER

BTS-P_MC_105_WADE TYPE
_FLUSH OUTLET

SCALE

NTS

DATE

15/08/2018



Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



WALKWAYS | BALCONIES | TERRACES