




DETAIL PROTECTION AND SURFACING



DETAIL PROTECTION AND SURFACING




MAIN AREA WATERPROOFING



NOTES

- 1 TRIFLEX CRYL PASTE OR TRIFLEX FLEXFILLER (REFER TO PROJECT SPECIFICATION)
- 2 OMIT THE TRIFLEX DECKFLOOR RS AND QUARTZ 50mm CENTRALLY TO THE SAW CRACK INDUCER




GENERAL NOTES

This drawing and any reference to structural / thermal elements should be treated as indicative only and read in conjunction with the Triflex Project specification proposal and relevant Triflex technical data. Details should be verified for accuracy and suitability as we specifically exclude any liability for errors, omissions or otherwise.

The drawing should not be reproduced or amended except with the written permission of Triflex. Do not scale, use figured dimensions only, and check all dimensions on site.

INDICATIVE SYSTEM BUILD-UP



SYSTEM

TRIFLEX DECKFLOOR WITH QUARTZ 0.7 - 1.2mm OR 0.4 - 1.2mm

PROJECT

STANDARD

DETAIL

CONTRACTION JOINT / CRACK INDUCER OVERBAND DETAIL

DRAWING NUMBER

DECKFLOOR WITH QUARTZ _070_CONTRACTION JOINT_CRACK INDUCER OVERBAND DETAIL

SCALE

NTS

DATE


13/08/2018

Triflex

Delivering solutions together

Triflex (UK) Limited

Whitebridge Way | Stone | Staffs
ST15 8JS | Tel: 01785 819119
www.triflex.co.uk | info@triflex.co.uk



CAR PARK | MARKINGS | REPAIRS