



Product data sheet

Triflex Powder Thixo (Stellmittel Pulver)

Use

Used as a powdered thickening / thixotropic agent for addition to Triflex products.

Properties

- Increases the viscosity where required
- Can be used with Triflex PMMA, PUR, EP and STPE systems

Components

Component	Product
Thixotropic agent	Triflex Powder Thixo

Packaging

Component	Pack size
Triflex Powder Thixo	Box: 1.00Kg
	Box: 5.00Kg

Colour(s)

White.

Mixing ratio

Up to to 4% depending on desired amount of thixotropy.

Mixing instructions

1. Evenly mix the Triflex Powder Thixo into the base resin;
2. Leave to stand for approximately 2-5 minutes for thixotropy to develop;
3. Mix products in accordance with Product Data Sheets.

Tool cleaning

Clean tools with Triflex Cleaner.

Storage / shelf life

Store unopened in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.



Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.