



Product data sheet

Triflex TecGrip 620

Use

Primer and adhesion promoter for use with Triflex SmartTec. This product can be used to pre-treat SmartTec layers where lapping to material that is 24 hours old and up to 100 days old. It should be checked on site whether pre-treatment on older surfaces is possible. Once the bonding agent has dried, it can be lapped / overlaid with Triflex SmartTec.

Properties

- Cold liquid applied
- 1 component
- Fast curing
- Easy application

Components

Component	Product
Resin	Triflex TecGrip 620

Packaging

Component	Pack size
Resin	Canister: 0.50L

Colour(s)

Orange / brown

Application conditions

Condition	Value
Ambient and substrate temperature	+5°C to +30°C

Substrate assessment / pretreatment / preparation

Ensure that the substrate is clean, dry and free from dust, laitance, grease, oil and any other contaminants and assess / pre-treat / prepare substrate in accordance with Triflex Project Specification proposal.

Application method

The bonding agent is applied by rolling it onto the surface where it forms a film. For vertical surfaces, the material must be applied in two work steps. Due to the intrinsic colour, it's important to ensure that the masking tape is placed as accurately as possible, especially with light background colours.

Note: Use masking tape to avoid staining of adjacent substrate.

Consumption

Approx. 0.10 L/m² on a smooth, even surface— refer to Triflex Project Specification proposal.

Note: Consumption based on smooth, even, non-absorbent substrate. Two applications are required on vertical surfaces.



Curing time (at 20°C)

Condition	Time
Can be over-coated	Approximately 25 minutes

Storage / shelf life

Store unopened in temperatures between +10°C and +30°C in a cool, dry, well ventilated place above freezing, out of direct sunlight and in the original container.

Shelf life if stored correctly: minimum 6 months.

Health and safety

Refer to Safety Data Sheets.

Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.

Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.