



# Triflex Catalyst

## Use

Powdered hardener for certain Triflex PMMA products. Refer to applicable product data sheet for specific requirements.

## Components

Component	Product
Catalyst	Triflex Catalyst

## Packaging

Component	Pack size
Catalyst	Bag: 0.10Kg (100g)
	Bag: 1.00Kg
	Box: 25.00Kg

## Colour

White.

## Measuring / mixing

Refer to Triflex Product Data Sheet for Triflex PMMA products.

**Note:** Ensure catalyst is fully dissolved in resin before application.

## Application method

Pour required amount into Triflex resin and mix in accordance with Triflex Product Data Sheet.

Refer to product data sheet of the PMMA resin being used.

## Consumption

Refer to Triflex Product Data Sheet for Triflex PMMA products.

## Storage / shelf life

Store in a closed container protected from contamination and in a dry place away from sources of ignition and heat at temperatures below +25°C. Protect from direct sunlight.

## Health and safety

Refer to Safety Data Sheets.

## Disposal information

Refer to Safety Data Sheets for recommended EWC waste codes.



## Notes

The advice we provide on the application of our products is based on extensive development work and many years of experience, and is given to the best of our knowledge. The wide variety of requirements for a building under the most diverse conditions mean that it is necessary for the contractor to test the product for suitability in each case. Triflex reserve the right to make alterations in keeping with technical developments or improvements.

Non-Triflex products must not be used with Triflex systems.

Only the most recent version of this data sheet is valid.